REVISION

Section review

## DISTRIBUTION STANDARD PNM

## Table IV Vertical Clearance of Wires, Conductors, and Cables Above Ground, Roadway, Rail, or Water Surfaces<sup>25</sup>

		Grounded Guys and Neutral Conductors	Multiplexed Cable	Open Wire Secondary	Phase Conductors on PNM Grounded Wye Distribution Systems
	Clearance of	<u>(ft)</u>	<u>(ft)</u>	<u>(ft)</u>	<u>(ft)</u>
Where Wires, Conductors, or Cables Cross Over or Overhang					
1.	Track rails of railroads (except electrified railroads using overhead trolly conductors) <sup>2, 16, 22</sup>	23.5	24.0	24.5	26.5
2.	Roads, streets and other areas subject to truck traffic <sup>23</sup>	15.5	16.0	16.5	18.5
3.	Driveways, parking lots, and alleys <sup>23</sup>	15.5 <sup>7, 13</sup>	16 <sup>7, 13</sup>	16.5 <sup>7</sup>	18.5
4.	Other land traversed by vehicles, such as cultivated, grazing, forest, orchard, etc. <sup>26</sup>	15.5	16.0	16.5	18.5
5.	Spaces and ways subject to pedestrians or restricted traffic only <sup>9</sup>	9.5	12.0 <sup>8</sup>	12.5 <sup>8</sup>	14.5
6.	Water areas not suitable for sailboating or where sailboating is prohibited <sup>21</sup>	14.0	14.5	15.0	17.0
7.	Water areas suitable for sailboating including lakes, ponds, reservoirs, tidal waters, rivers, streams, and canals with unobstructed surface are of: 17, 18, 19,20,21				
	(a) Less than 20 acres (b) 20 to 200 acres (c) 200 to 2,000 acres (d) Over 2,000 acres	17.5 25.5 31.5 37.5	18.0 26.0 32.0 38.0	18.5 26.5 32.5 38.5	20.5 28.5 34.5 40.5
8.	(d) Over 2,000 acres Established boat ramps and associated rigging areas; areas posted with sign(s) for rigging or launching sail boats	Clearance above ground shall be 5' greater than in 7 above, for the type of water areas served by the launching site			

Vertical Clearances Above Ground, Roadway, Rail, or Water Surfaces

**DS-13-2.5 Page 1** E
11/01/05