APPENDIX 1 to LGIP INTERCONNECTION REQUEST FOR A LARGE GENERATING FACILITY

- 1. The undersigned Interconnection Customer submits this request to interconnect its Large Generating Facility with Transmission Provider's Transmission System pursuant to a Tariff.
- 2. This Interconnection Request is for (check one):
 - A proposed new Large Generating Facility.
 - _____ An increase in the generating capacity or a Material Modification of an existing Generating Facility.
 - Permissible Technological Advancement to an existing Large Generation Interconnection Request.
 - _____ Surplus Interconnection Service at an existing Point of Interconnection
- 3. The type of interconnection service requested (check one):
 - _____ Energy Resource Interconnection Service
 - _____ Network Resource Interconnection Service
- 4. Interconnection Customer provides the following information:
 - a. Address or location or the proposed new Large Generating Facility site (to the extent known) or, in the case of an existing Generating Facility, the name and specific location of the existing Generating Facility;
 - b. Maximum summer at _____ degrees C and winter at _____ degrees C megawatt electrical output of the proposed new Large Generating Facility or the amount of megawatt increase in the generating capacity of an existing Generating Facility;
 - c. General description of the equipment configuration;
 - d. Commercial Operation Date (Day, Month, and Year);
 - e. Name, address, telephone number, and e-mail address of Interconnection Customer's contact person;
 - f. Approximate location of the proposed Point of Interconnection (optional); and
 - g. Interconnection Customer Data (set forth in Attachment A)
 - h. Primary frequency response operating range for electric storage resources.
 - i. Requested capacity (in MW) of Interconnection Service (if lower than the Generating Facility Capacity).

- 5. Applicable deposit amount as specified in the LGIP.
 - \$75,000 for requests of less than 50 MW
 - \$150,000 for requests of 50 MW and Greater, but less than 200 MW
 - \$250,000 for requests of 200 MW and greater
 - \$10,000 for Permissible Technological Advancement Request.
- 6. Type of Interconnection Study Requested
 - _____ Preliminary Interconnection System Impact Study
 - _____ Definitive Interconnection System Impact Study
- 7. For application to the Definitive Interconnection System Impact Study Queue, point of delivery to deliver to adjoining Control Area if the Generating Facility is not designated a Network Resource pursuant to Section 30.2 of the OATT.
- 8. Evidence of Site Control as specified in the LGIP (check one)
 - Is attached to this Interconnection Request
 - Will be provided at a later date in accordance with this LGIP (only applicable to the Definitive Interconnection System Impact Study)
- 9. This Interconnection Request shall be submitted to the representative indicated below:

Public Service Company of New Mexico Director, Transmission/Distribution Planning and Contracts Mail Stop Z220 2401 Aztec Rd., NE Albuquerque, NM 87107

10. Representative of Interconnection Customer to contact:

[To be completed by Interconnection Customer]

11. This Interconnection Request is submitted by:

Name of Interconnection Customer:

By (signature):

Name (type or print):

Title:

Date:

Attachment A to Appendix 1 **Interconnection Request**

LARGE GENERATING FACILITY DATA

UNIT RATINGS

kVA	°F	_Voltage
Power Factor		
Speed (RPM)		Connection (e.g. Wye)
Short Circuit Ratio		Frequency, Hertz
Stator Amperes at Ra	ated kVA	Field Volts
Max Turbine MW	°F	F
Primary frequency re	sponse operatin	ng range for electric storage resources:
Minimum State of Cl	harge:	
Maximum State of C	harge:	

COMBINED TURBINE-GENERATOR-EXCITER INERTIA DATA

Inertia Constant, H =	kW sec/kVA	
Moment-of-Inertia, $WR^2 =$	lb. ft. ²	2

REACTANCE DATA (PER UNIT-RATED KVA)

DIRECT AXIS

QUADRATURE AXIS

Synchronous - saturated	X_{dv}	 X_{qv}	
Synchronous - unsaturated	X_{di}	 X_{qi}	
Transient - saturated	X'_{dv}	 X'qv	
Transient - unsaturated	X'di	 X'qi	
Subtransient - saturated	X" _{dv}	 X" _{qv}	
Subtransient - unsaturated	X"di	 X"qi	
Negative Sequence - saturated	$X2_v$		
Negative Sequence - unsaturated	$X2_i$		
Zero Sequence - saturated	$\rm X0_v$		
Zero Sequence - unsaturated	$X0_i$		
Leakage Reactance	Xl_m		

FIELD TIME CONSTANT DATA (SEC)

Open Circuit	T'do	 T'qo	
Three-Phase Short Circuit Transient	T' _{d3}	 T'q	
Line to Line Short Circuit Transient	T'd2		
Line to Neutral Short Circuit Transient	T'd1		
Short Circuit Subtransient	T" _d	 T"q	
Open Circuit Subtransient	T" _{do}	 T" _{qo}	

ARMATURE TIME CONSTANT DATA (SEC)

Three Phase Short Circuit	T _a 3	
Line to Line Short Circuit	T_{a2}	
Line to Neutral Short Circuit	T_{a1}	<u>-</u>

NOTE: If requested information is not applicable, indicate by marking "N/A."

MW CAPABILITY AND PLANT CONFIGURATION LARGE GENERATING FACILITY DATA

ARMATURE WINDING RESISTANCE DATA (PER UNIT)

Positive	\mathbf{R}_1	_
Negative	R_2	
Zero	R_0	

Rotor Short Time Thermal Capacity $I_2^2t =$ _____ Field Current at Rated kVA, Armature Voltage and PF = ______ amps Field Current at Rated kVA and Armature Voltage, 0 PF = ______ amps Three Phase Armature Winding Capacitance = _____ microfarad Field Winding Resistance = _____ ohms _____ °C Armature Winding Resistance (Per Phase) = _____ ohms _____ °C

CURVES

Provide Saturation, Vee, Reactive Capability, Capacity Temperature Correction curves. Designate normal and emergency Hydrogen Pressure operating range for multiple curves.

GENERATOR STEP-UP TRANSFORMER DATA RATINGS

Capacity	Self-cooled/	
1 2	Maximum Nameplate	
	/ kVA	
Voltage Ratio(Generator Side/System side/Tertiary	7)
	/ / /	kV
-		
Winding Conne	ections (Low V/High V/Tertiary V	(Delta or Wye))
	/ / / /	
	<u> </u>	
Fixed Taps Ava	ailable	
r mea raps rive		_
Present Tap Set	tting	
riesent rup set		
If more than on	e transformer stage is used to deliv	er the output from the proposed generator to
	0	1 1 0
		ation above for each transformer or
transformer typ	e.	

IMPEDANCE

Positive	Z ₁ (on self-cooled kVA rating)	_ %	X/R
Zero	Z ₀ (on self-cooled kVA rating)	_ %	X/R

EXCITATION SYSTEM DATA

Identify appropriate IEEE model block diagram of excitation system and power system stabilizer (PSS) for computer representation in power system stability simulations and the corresponding excitation system and PSS constants for use in the model.

GOVERNOR SYSTEM DATA

Identify appropriate IEEE model block diagram of governor system for computer representation in power system stability simulations and the corresponding governor system constants for use in the model.

WIND GENERATORS

Number of generators to be interconnected pursuant to this Interconnection Request:

Elevation: _____ Single Phase ____ Three Phase

Inverter manufacturer, model name, number, and version:

List of adjustable setpoints for the protective equipment or software:

Note: A completed General Electric Company Power Systems Load Flow (PSLF) data sheet or other compatible formats, such as IEEE and PTI power flow models, must be supplied with the Interconnection Request. If other data sheets are more appropriate to the proposed device, then they shall be provided and discussed at Scoping Meeting.

INDUCTION GENERATORS

(*) Field Volts:
(*) Field Amperes:
(*) Motoring Power (kW):
(*) Neutral Grounding Resistor (If Applicable):
(*) I ₂ ² t or K (Heating Time Constant):
(*) Rotor Resistance:
(*) Stator Resistance:
(*) Stator Reactance:
(*) Rotor Reactance:
(*) Magnetizing Reactance:
(*) Short Circuit Reactance:
(*) Exciting Current:
(*) Temperature Rise:
(*) Frame Size:
(*) Design Letter:
(*) Reactive Power Required In Vars (No Load):
(*) Reactive Power Required In Vars (Full Load):
(*) Total Rotating Inertia, H: Per Unit on KVA Base

Note: Please consult Transmission Provider prior to submitting the Interconnection Request to determine if the information designated by (*) is required.