



Detail

NOTES

- (1) Level luminaire in accordance with manufacturer's instructions.
- (2) Minimum recommended mounting height is 28'.

REFERENCES

- (1) See DS-2-11.0 Three-Phase Tangent and Small Angles
- (2) See DS-3-1.0 Secondary Tangent Structure
- (3) See DS-12-1.0 Lamp and Photo Control Identification Coding

Base Material List

Item	Quan.	Description	Stock #
A	1	250W HPS Luminaire	0000-000516
B	1	250W HPS Lamp	6240-312717
C	1	6' Wood Pole Bracket	5975-260935
G	1	5/8" MF Locknut	5310-153506
H	2	1/2" x 4" Lag Screw	5305-147794
J	1	2 1/4" Square Washer	5310-153571
K	1	5/8" x 1/2" Machine Bolt	DS-18-25.0
L	2	5/8" Line Tap	DS-18-99.0
M	1	5/8" Double Coil Spring Washer	5310-163034

Material List with Photo Control

D	1	105-305V Photo Electric Control	0000-005649
E	8'	#8 THW White Wire	6145-000334
F	8'	#8 THW Black Wire	6145-000292

Material List without Photo Control

D	1	Shorting Cap	7000-192500
E	2'	#8 THW White Wire	6145-000334
F	16'	#8 THW Black Wire	6145-000292